



Specifications

Model number	M500-528-#K-V24-R90-NWP-B8
LED Type	COB
LED Qty (pcs/m)	528 pcs/m
Colour Availability	2700K, 4000K, 6500K
Ra	>90
Work Voltage	24V DC
Peak Power (w/m)	12W per meter
Power Per Roll (5m)	60W
SDCM	3 Step
Lumen (Lm)	1000-1100Lm

Cutting Unit	Free Cutting
Adhesive Tape	3M 9495LE 300MP
PCB Type	2 oz
Dimensions	5000mm x 8mm (Roll)
Package	5m per package
Max Run Length	5m without connector
IP Grade	IP20/TWPJ
Certification	cULus, CE, RoHS
Operating Temp	-25 to +40°C
Max Case Temp	75°C

Colour Availability

2700K – Warm White
4000K – Natural White
6500K - White

Packaging Information

5 Meters per roll, 1 roll per bag (*Custom lengths less than 5m as per customer request*)

Precautions

- Do not bend the LED strip into an arc with a diameter less than 60mm. Bending the LED strip to a radius of 60mm or less may cause damage or failure
- Do not fold the LED strip. Folding the LED strip can cause damage or failure
- Risk of electric shock, installation of this strip light using hard wired drivers to be done by qualified electrician only. All strips should be inspected prior to connection to power. For DIY projects, plug-in 24V drivers may be utilized.
- Make sure the power supply voltage meets the 24V requirements of the strip and that all components are accurately connected prior to switching on the power
- Keep LED strip away from wet or damp conditions